



#### 01 Cyclone Systainer

The Festool CT pre-separator with Cyclone technology separates and collects coarse and fine dust, before they enter the mobile dust extractor. The dust-laden air is forced into a spiral motion in the Cyclone, causing the particles to impact against the wall of the Cyclone and fall into the CT pre-separator's collection container.

#### 02 Clever collection container

The transparent collection container makes it easy to see how full it is.



#### 03 Convenient dust disposal

Good grips make disposing of high volumes of dust an easy job.



#### 04 Flexible in use

The mobile dust extractor and CT pre-separator can be connected easily using the SYS-Dock system.



#### 05 Modular design

The modular design enables easy transportation and cleaning of the individual parts.



# FESTOOL

## CT pre-separator CT-VA-20

Valid from 01.09.2018


### Flyer

#### Festool UK Ltd

Saxham Business Park  
Saxham  
Bury St Edmunds  
Suffolk  
IP28 6RX  
Great Britain  
Phone: +44 (0) 1284 760 791  
Fax: +44 (0) 1284 702 156  
E-mail: [info@festool.co.uk](mailto:info@festool.co.uk)

[www.festool.co.uk](http://www.festool.co.uk)

Dealers



Item no. 67893 GB/en



4 014549 335833

Vibration levels and emission values can be found in the operating instructions at [www.festool.co.uk](http://www.festool.co.uk)

Subject to changes. All images are non-binding.  
Produced for Festool GmbH, 73240 Wendlingen,  
05/2018



Efficient,  
simple and reliable.

## Handles high volumes of dust.

The new CT pre-separator  
with Cyclone technology.



Tools for the toughest demands

# The most efficient way of coping with high dust volumes.

High volumes of dust, shavings and chips are now no longer a problem. Neither for the main filter or the suction power. The pre-separator, which is compatible with Festool CT mobile dust extractors, collects up to 95% of dust before it reaches the mobile dust extractor. This reduces the load on the main filter and ensures consistently high suction power throughout the work process.



## Powerful

- › Copes with high volumes of dust thanks to cyclone technology
- › Up to 80% of mineral dust and up to 95% of coarse particles, such as sawdust are separated and collected in the container
- › Consistently high suction power as a result of reducing the load on the main filter
- › Efficient operation with consistent suction power
- › Approved for dust categories L and M

## Convenient

- › Easy and safe to transport due to the stackable collection container's compact dimensions and sturdy design
- › Good grips on the collection container make disposing of high volumes of dust an easy and clean job
- › The transparent collection container makes it easy to see how full it is
- › The modular design enables easy cleaning of the individual parts

## Sturdy

- › Ideal for demanding everyday use on construction sites
- › Long service life thanks to sturdy components

## A perfect system




- › Retrofitting Festool mobile dust extractors is simple
- › The mobile dust extractor and CT pre-separator can be connected easily using the SYS-Dock system
- › Compatible with Festool CT 26/36/48 mobile dust extractors – depending on application with or without AC cleaning.
- › Flexible operation with or without CT pre-separator depending on the application
- › Additional socket for plug-it suction hoses and power tools

Items included	Order no.
For all Festool CT 26/36/48 dust extractors with and without AUTOCLEAN function	
<b>CT-VA-20 pre-separator</b>	204083
Cyclone Systainer, VAB-20 collection container, Systainer tub, connecting hose, disposal bag, vessel cover	
Accessories	Order no.
<b>ENS-VA-20/10 disposal bag</b>	204296
For use in the Festool CT-VA-20 pre-separator collection container, max. container volume 20 l, for dusts in dust classes L and M, 10 pcs.	
<b>VAB-20 collection container</b>	
max. container volume 20 l	
1 pc. collection container including cover	204294
3 pc. collection container including cover	204295
<b>CT-VA AK EU connecting cable</b>	575667
for retrofitting the CT-VA pre-separator with additional power socket; particularly suitable for use with plug-it suction hose. Max. wattage 2,400 W, cable length 0.85 m	

## Mineral particulates

### Typical applications

Ideal in combination with the CTL/CTM mobile dust extractors\* 26/36/48 with AUTOCLEAN function and with the following tools:

		
PLANEX and PLANEX easy** long-reach sanders	RENOFIX RG 130 diamond grinder	RENOFIX RG 80 and RG 150 refurbishment millers

## Coarse dust (sawdust/shavings/chips)

### Typical applications

Ideal in combination with the CTL/CTM mobile dust extractors\* 26/36/48 with and without AUTOCLEAN function and with the following tools:

		
OF 2200 router	HK 85 circular saw	IS 330, SSU 200, ISC 240 sword and insulation saws

\* The CT-VA pre-separator is approved for dust classes L and M.  
\*\* When using the CT-VA pre-separator, the PLANEX Classic suction support is reduced.