








































# VECTURO OSC 18 cordless oscillator

## Overview of consumables

Description		Type	Blade shape	Tool holder	Dimensions	Order no.	Applications
WOOD	<b>Saw blade</b> Authentic double-rowed Japan toothing for high-precision cuts and clean cutting edges in wooden materials. <b>Attention:</b> plunge cuts not possible.		offset	<b>STARLOCK</b>	50 × 35 mm	203333	 Solid wood
			straight	<b>STARLOCK PLUS</b>	50 × 65 mm	203332	 Raw/treated particle board
	<b>Saw blade</b> Made from premium quality bimetal for long, straight cuts and cut-outs in laid parquet and laminate.		straight	<b>STARLOCK PLUS</b>	Ø 100 mm	203334	 Solid wood  Raw/treated particle board  Laminate/parquet
UNIVERSAL	<b>Saw blade</b> Made from premium quality bimetal. Particularly durable and robust. Ideal for plunge cuts. For working with wood, treated wood, painted wood, composite materials, fibre-reinforced plastics, plasterboard, non-ferrous metals, plastics.		offset	<b>STARLOCK</b>	50 × 35 mm	203338	 Wood with nails
			straight	<b>STARLOCK PLUS</b>	50 × 65 mm	203960	 Raw/treated particle board
			offset	<b>STARLOCK MAX</b>	78 × 32 mm	203337	 Fibre-reinforced plastics
			offset	<b>STARLOCK MAX</b>	78 × 42 mm	203336	 Epoxy  Gypsum fibre or fibre-bonded materials/aerated concrete  Non-ferrous metals
METAL & BUILDING MATERIALS	<b>Saw blade</b> The carbide saw blade with an additional ceramic coating boasts incredibly high wear resistance and a wide range of applications. It is perfect for sawing hard materials such as ferrous metals, stainless steel or copper pipes. It is also suitable for abrasive materials such as façade panels or brick.		offset	<b>STARLOCK</b>	40 × 32 mm	578095	 Hard materials, steel
			offset	<b>STARLOCK PLUS</b>	60 × 32 mm	578096	 Non-ferrous metals  Construction timber with screws  Construction timber with mortar  Fibre-reinforced plastics  Epoxy  Gypsum fibre or fibre-bonded materials/aerated concrete
SPECIAL	<b>Diamond saw blade</b> For cutting marble joints, epoxy resin joints, trass joints, hard epoxy and cement joints.		straight	<b>STARLOCK PLUS</b>	Ø 90 mm	204414	 Epoxy  Joints
	<b>Rigid scraper</b> For removing tile adhesive, old paint, adhesive residue, carpeted floor and underfloor coatings.		straight	<b>STARLOCK PLUS</b>	60 × 52 mm	204412	 Adhesive  Silicone
	<b>Silicone blade</b> For removing soft materials such as silicone, acrylic and putty from joints.		straight	<b>STARLOCK</b>	35 × 70 mm	578097	 Silicone  Window kit
	<b>Segment saw blade</b> For removing window glass.		straight	<b>STARLOCK MAX</b>	32 mm	204410	 Plastics  Window kit

**Starlock:** the tool holder for maximum force transmission.

**STARLOCK**   **STARLOCK PLUS**   **STARLOCK MAX**

The Festool VECTURO OSC 18 cordless oscillator features a StarlockMax tool holder, making it compatible with the entire range of Starlock accessories.

The three-dimensional tool holder guarantees a perfect fit for the saw blade and maximum force transmission for even the toughest jobs.



GB/en